

Classification

- A. Managerial desks
- B. Office desks
- C. Conference desks

A. Managerial desks**A.1. Technical Data of Managerial desks**

- A.1.1. All desk tops have a thickness of 38 mm (25 mm for the modesty panel) and are made of double-side melamine film coated 3-layer chipboard E1.
- A.1.2. All managerial desks consist of two side legs which are connected together through the modesty panel - beam, thus forming an “H”-shaped base. The desktop is placed over the base with insertion of special plastic connecting elements, which create a visual gap of 12mm between the desktop and the base.
- A.1.3. The visible edges are covered with 2 mm thick edge-banding, while the non-visible edges are covered with 0,45 mm thick edge-banding.
- A.1.4. Cable routing is possible through a cable grommet on the desktop surface and cable channel inside the modesty panel or under the desktop surface (optional).
- A.1.5. Each side leg has on the bottom, two aluminium glides in inverse “Π” shape.
- A.1.6. The modesty panel can be made either of 25 mm thick melamine chipboard, or of 25 mm thick melamine chipboard with a lacquered extra clear glass surface of 4 mm thickness glued on it, or made of 1,5 mm thick steel sheet, suitably formed and powder coated.
- A.1.7. The auxiliary surface, with suitable spacers made of reinforced polyamide can have an extra clear glass surface of 4 mm thickness, lacquered or transparent, glued on it.

Packaging 1 Managerial desk LYSIS PLUS, 1700 x 2000 mm,
Weight: 121,0 kg
Volume: 0.28 m³
Packets: 6

Packaging 1 Managerial desk LYSIS PLUS, 1700 x 900 mm,
Weight: 72,0 kg
Volume: 0.15 m³
Packets: 6

PRODUCT CERTIFICATES:

-

B. Office desks

B.1. Technical Data of Office desks

- B.1.1. All desk tops have a thickness of 38mm (25mm for the modesty panel) and are made of double-side melamine film coated 3-layer chipboard E1.
- B.1.2. All office desks consist of two side legs which are connected together through the modesty panel - beam, thus forming an “H”-shaped base. The desktop is placed over the base.
- B.1.3. The visible edges are covered with 2 mm thick edge-banding, while the non-visible edges are covered with 0,45 mm thick edge-banding.
- B.1.4. Cable routing is possible through a cable grommet on the desktop surface and cable channel inside the modesty panel or under the desktop surface (optional).
- B.1.5. Each side leg has on the bottom two glides in inverse “Π” shape, made of reinforced polyamide, for correct and safe leveling of the desk.
- B.1.6. The leg for surface extension is made of steel tube with 50 mm diameter and 2 mm thickness. It has a steel top plate of 5mm thickness and a leveling adjusting screw and is powder coated.



Packaging 1 Office desk LYSIS PLUS, 1800 x 900mm,

Weight: 75,0 kg

Volume: 0.18 m³

Packets: 3

PRODUCT CERTIFICATES:

-

C. Conference desks

C.1. Technical Data of Conference desks

C.1.1. All desk tops have a thickness of 38 mm and are made of double-side melamine film coated 3-layer chipboard E1, with 2 mm thick edge-banding material.

C.1.2. All conference desks have a support frame made of powder coated steel tubes of rectangular cross section 20x40x2 mm.

C.1.3. The vertical supports are made of powder coated steel tube of rectangular cross section 45x45x1,5 mm.

C.1.4. Cable routing is possible through cable grommets on the desktop surface and cable channel under the desktop surface (optional).

C.1.5. The connecting junctions between the horizontal and the vertical elements are made of die-cast aluminium and connect the elements in a non-visible manner.

Sizes, shapes and surface colours from the DROMEAS catalogue

Packaging 1 Conference desk LYSIS PLUS, 1800 x 900 mm,

Weight: 66,0 kg

Volume: 0.44 m³

Packets: 2

PRODUCT CERTIFICATES:



